



# Technical specification bucket


## JET 56 P



Jokey Euro Tainer Profi

### dimensions

D1: 227,0 mm  
 D2: 210,0 mm  
 D3: 191,0 mm  
 H:\* 194,0 mm  
 \*Height without lid




basic data	volume to rim:	6,00 l	handle types	metal handle	21,0 g	tolerances	dimensions:	+/- 1 mm
	weight:	150,0 g	plastic handle		10,0 g		volume/weight:	+/- 5 %
	weight group:	Medium	belt handle		-			
			no handle		-			
			body grip		-			
			roller grips		-			

decoration	Digital	IML	offset
height:	135,0 mm	172,8 mm	135,0 mm
width:	625,0 mm	636,1 mm	610,0 mm
median breadth:			625,0 mm

Lid	DET 225 P	FDET 225 P	FDET 225 P	DET 56 P	DET 225 PR
	standard	sealing lid	sealing lid	standard	shaker lid
stacking height two f	379,0 mm	0,0 mm	395,0 mm	376,5 mm	379,0 mm
each further:	185,0 mm	0,0 mm	194,0 mm	182,5 mm	185,0 mm

logistic	Max. compression for standard lid at 20°C on the lowest pail: 25,00 kg
<b>pieces per pallet</b>	<b>EUP (Europallet)</b>
Bucket	1080
pallet height	2,20 m
layer quantities: 18	80 cm (31,5'') x 120 cm (47,24'')



### material



### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



# Technical specification lid DET 225 P



## dimensions

D1: 223,0 mm  
H: 12,0 mm

## basic data

displaced volume:: 0,30 l  
weight: 35,0 g  
weight group: Medium

## tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

## decoration

Diameter

## IML

194,0 mm

## offset

182,0 mm

## Bucket




## logistic

### pieces per pallet

Lid 5400  
pallet height 2,20 m  
layer quantities: 18

### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



## material



### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

## misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 25.04.2017 rev. 2.2



# Technical specification lid

## FDET 225 P



### dimensions

D1: 222,0 mm  
H: 19,0 mm

### basic data

displaced volume:: 0,00 l  
weight: 35,0 g  
weight group: Medium

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

0,0 mm

### offset

0,0 mm

### Bucket




### logistic

#### pieces per pallet

Lid 4800  
pallet height 2,20 m  
layer quantities: 18

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 16.05.2017 rev. 2.3



# Technical specification lid

## FDET 225 P



### dimensions

D1: 222,0 mm  
H: 19,0 mm

### basic data

displaced volume:: 0,00 l  
weight: 32,0 g  
weight group: Light

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

0,0 mm

### offset

0,0 mm

### Bucket




### logistic

#### pieces per pallet

Lid 4800  
pallet height 2,20 m  
layer quantities: 18

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 26.08.2016 rev. 2.1



# Technical specification lid DET 56 P



## dimensions

D1: 223,0 mm  
H: 12,0 mm

## basic data

displaced volume:: 0,35 l  
weight: 35,0 g  
weight group: Medium

## tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

## decoration

Diameter

## IML

0,0 mm

## offset

0,0 mm

## Bucket

JET 53 PC



JET 56 P



JET 55 PC




## logistic

### pieces per pallet

Lid 5400  
pallet height 2,20 m  
layer quantities: 18

### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



## material



### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

## misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 09.03.2015 rev. 2.0



# Technical specification lid DET 225 PR



### dimensions

D1: 223,0 mm  
H: 12,0 mm

### basic data

displaced volume:: 0,30 l  
weight: 38,0 g  
weight group: Medium

### tolerances

dimensions: +/- 1 mm  
volume/weight: +/- 5 %

### decoration

Diameter

### IML

0,0 mm

### offset

0,0 mm

### Bucket

JET 44 P



JET 53 P



JET 53 PC



JET 56 P



JET 62 P




### logistic

#### pieces per pallet

Lid 5400  
pallet height 2,20 m  
layer quantities: 18

#### EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



### material



#### QM / certificates

You can download our current certificates on [www.jokey.com](http://www.jokey.com).

### misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at [www.jokey.com](http://www.jokey.com) or via email [info@jokey.com](mailto:info@jokey.com)

Date: 26.08.2016 rev. 2.1